



Qingdao Empire Machinery Co., Ltd (EME)

Address: No. 50 Suzhou Road Jiaozhou Qingdao City Shandong Province, China

TEL: +86 532 87237613

FAX: +86 532 87210193

Web: www.eme-machinery.com

Living Cattle Pneumatic Fixed Killing Box {Model: QE-C104-I}



Qingdao Empire Machinery Co., Ltd (EME)

Address: No. 50 Suzhou Road Jiaozhou Qingdao City Shandong Province, China

Tel: +532 87237613

Fax: +532 87210193

Website: www.eme-machinery.com





Qingdao Empire Machinery Co., Ltd (EME)

Address: No. 50 Suzhou Road Jiaozhou Qingdao City Shandong Province, China

TEL: +86 532 87237613

FAX: +86 532 87210193

Web: www.eme-machinery.com

Machine Name		Living Cattle Pneumatic Fixed Killing Box			
Model	QE-C104-I	Origin	China		
Max Capacity	40Cattle Per Hour				
Design Principle	Pneumatic Controlling				
Characteristic	Which main used to limited living cattle/horse for killing and fasten hind leg lifting to bleeding pipe convey rail for complete bleeding.				
Operation Instruction	<ol style="list-style-type: none"> 1、 The living cattle get inside of reversed box through a living cattle leading machine, then closed the entrance door to limited cattle moving. 2、 The user turn on air pressure switch, meanwhile one side of button panel will be slowly dropping down and seam side wall panel will get up through air pressure cylinder. 3、 When the hind legs of cattle complete sliding out of machine then killing and fasten with bleeding shackle and lifting to bleeding pipe rail for complete bleeding 				
Maintain Instruction	<ol style="list-style-type: none"> 1、 When the equipment complete finished installation in right position then flap box bolt connection can be. While ensuring cylinder pipe connection seal and smooth 2、 The staffs should avoid impact and damage the cylinder in working, the fasteners should be solid and reliable and in each class after the shutter box rinse. Opponents control valve should be avoided too much force 				
					
					
Characteristic	Stability & Quick		Low Noise		Easy Maintenance
Electrical	Voltage(V) 380/220		Frequency(HZ) 50-60		Power(KW)
Consumption	Water(L/Shift)		Compressed Air (L/T) 8		Steam(Kg/H)
Out-Size And Weight	L(MM) 2800	W(MM) 1800	H(MM) 2000	Weight(Kg) 1150	
Material	Hot Galvanized Mainly Frame And Panel			Alloy Gas Party	
Components	Reversed Machine		Head Folder Device		Air Cylinders
Remark	Working Pressure		6MPA		



Qingdao Empire Machinery Co., Ltd (EME)

Address: No. 50 Suzhou Road Jiaozhou Qingdao City Shandong Province, China

TEL: +86 532 87237613

FAX: +86 532 87210193

Web: www.eme-machinery.com

Cylinder Data

- 1、 TQGB160X200-CA
- 2、 Max Stroke Of Door Cylinder: 350MM
- 3、 Max Stroke Of Side Panel: 1100MM